

Constant Humidity Machine



- Ambient temperature humidity display timely
- 3 minutes delay start protection
- Phase sequence error/phase missing protection
- Refrigerant low pressure protection,Eco-friendly refrigerant
- Error code display timelySupport function of Rs485 connection for multiple units controlling
- Support function of ventilation mode
- Continuously drain with hose connection
- Automatically defrosting

DJHS-2E



Model number	DJHS-2E	Working temperature range	5~38℃
Dehumidifying capacity		Applicable area	10-15m²
(27℃ , RH60%)	23L/24h	Panel adjustable humidity	RH10%-95%
Dehumidifying capacity		Noise	≤ 45dB
(30℃ , RH80%)	58L/24h	Drainage way	Hose connection
Humidification	2-3L/h	Warranty	1 year
Circulating air volume	650m³/h	Standard packaging	Wooden Case
Power supply	220V/50Hz	Net weight	51kg
Input power	0.9kW	External dimensions	450*560*870mm
Current	4.2A		

DJHS-3E / DJHS-5E

Model number	DJHS-3E	DJHS-5E
Dehumidifying capacity		
(27℃ , RH60%)	42L/24h	70L/24h
Dehumidifying capacity		
(30℃ , RH80%)	90L/24h	150L/24h
Humidification	3-5L/h	6-8L/h
Circulating air volume	1000m³/h	1100m³/h
Power supply	220V/50Hz	220V/50Hz
Input power	1.5kW	1.8 kW
Current	7A	8.5A
Working temperature range	5~38℃	5~38℃
Applicable area	30-40m²	40-50m²
Panel adjustable humidity	RH10%-95%	RH10%-95%
Noise	≤ 60dB	≤ 60dB
Drainage way	External hose	External hose
Warranty	1 year	1 year
Standard packaging	Wooden case	Wooden Case
Net weight	80.5kg	80.5kg
External dimensions	547*498*1380mm	547*498*1380mm



Constant Humidity Machine

Model number	DJHS-7E	DJHS-10E
Dehumidifying capacity		
(27℃, RH60%)	90L/24h	120L/24h
Dehumidifying capacity		
(30℃, RH80%)	168L/24h	240L/24h
Humidification	7-9L/h	10-12L/h
Circulating air volume	2000m³/h	2800m³/h
Power supply	380V/50Hz	380V/50Hz
Input power	3.0kW	3.8kW
Current	6.0A	7.6A
Working temperature range	5~38℃	5~38℃
Applicable area	60-80m²	100-120m²
Panel adjustable humidity	RH10%-95%	RH10%-95%
Noise	≤ 65dB	≤ 65dB
Drainage way	Hose connection	Hose connection
Warranty	1 year	1 year
Standard packaging	Wooden Case	Wooden Case
Net weight	140kg	160kg
External dimensions	632*510*1768mm	805*500*1780mm

- Ambient temperature humidity display timely
- 3 minutes delay start protection
- Phase sequence error/phase missing protection
- Refrigerant low pressure protection,Eco-friendly refrigerant
- Error code display timelySupport function of Rs485 connection for multiple units controlling

DJHS-10E

DJHS-7E



- Support function of ventilation mode
- Continuously drain with hose connection
- Automatically defrosting

DJHS-15E



Model number	DJHS-15E
Dehumidifying capacity	
(27℃, RH60%)	200L/24h
Dehumidifying capacity	
(30℃, RH80%)	388L/24h
Humidification	12-15L/h
Circulating air volume	4000m³/h
Power supply	380V/50Hz
Input power	5.5kW
Current	11.0A
Working temperature range	5~38℃
Applicable area	200-250m²
Panel adjustable humidity	RH10%-95%
Noise	≤ 65dB
Drainage way	Hose connection
Warranty	1 year
Standard packaging	Wooden Case
Net weight	200kg
External dimensions	1320*700*1830mm