

CONLOON



CLR-400

Model	CLR-600
Dehumidify capacity(20°C, 60%)(kg/hr)	3kg/hr
Process Air Flow (m³/h)	580
Inlet Size (mm)	125
Reactivation Air Flow (m³/h)	200
Outlet Size (mm)	80
Applied Temperature	-10°C-50°C
Max Power(KW)	4.5KW
Warranty	1year
Voltage	220V/50Hz/1Ph
Current	20A
Packing Dimension (mm)	685*505*1040
Weight(kg)	65

Model	CLR-400
Dehumidify capacity(20°C, 60%)(kg/hr)	2.5kg/hr
Process Air Flow (m³/h)	400
Inlet Size (mm)	125
Reactivation Air Flow (m³/h)	130
Outlet Size (mm)	80
Applied Temperature	-10°C-50°C
Max Power(KW)	2.3KW
Warranty	1year
Voltage	220V/50Hz/1Ph
Current	10A
Packing Dimension (mm)	590*420*900
Weight(kg)	45



CLR-600



CLR-750

Model	CLR-750
Dehumidify capacity(20°C, 60%)(kg/hr)	4.5kg/hr
Process Air Flow (m³/h)	750
Inlet Size (mm)	125
Reactivation Air Flow (m³/h)	250
Outlet Size (mm)	125
Applied Temperature	-10°C-50°C
Max Power(KW)	7KW
Warranty	1year
Voltage	380V/50Hz/3Ph
Current	14A
Packing Dimension (mm)	1090*600*671
Weight(kg)	90



CLR-1000



CLR-1500



CLR-3000

Model	CLR-1000	CLR-1500	CLR-3000
Dehumidify capacity(20°C, 60%)(kg/hr)	7.5kg/hr	10kg/hr	19kg/hr
Process Air Flow (m³/h)	1100	1550	3000
Inlet Size (mm)	200	250	400/488*222
Reactivation Air Flow (m³/h)	400	580	1100
Outlet Size (mm)	150	160	200
Applied Temperature	-10°C-50°C		
Max Power(KW)	15KW	16KW	30KW
Warranty	1year	1year	1year
Voltage	380V/50Hz/3Ph		
Current	18A	26A	60A
Packing Dimension (mm)	950*710*1200	880*696*1234	1312*859*1300
Weight(kg)	180	202	340